

16131.5 Pyranometer



POSSIBLE APPLICATIONS

- PV system performance monitoring
- Professional solar measurements
- Simulated solar tests (laboratory)
- Meteorological networks

First Class Pyranometer

The 16131.5 series pyranometers are high-precision digital solar radiation sensors that meet the requirements of "First Class" according to the WMO guidelines and "Spectrally Flat Class B" according to ISO 9060:2018.

Model 00.16131.501030 is equipped with an on-board heater and thus meets the requirements for Class B PV monitoring systems in accordance with IEC 61724-1:2017.

The 16131.5 measures the solar radiation received by a flat surface in W/m^2 from a viewing angle of 180° . Various digital and analog outputs are available for easy integration.

- Highest measurement accuracy in the "First Class" category
- Improved response time
- With integrated heating, version 00.16131.501030 meets the requirements of IEC 61724-1 Class B.



PRODUCT OVERVIEW

16131.5 Pyranometer

Professional Line	16131.5
Ident-No.	00.16131.501040: Digital sensor with analog 4-20 mA output 00.16131.501000: Analog sensor with passive millivolt (mV) output
Measuring ranges	0...3000 W/m ² Global radiation in the spectral range 285...3000 nm
Directional response	< ± 20 W/m ²
Resolution	0.01 W/m ²
Spectral sensitivity	< ± 3% (0.35...1.5 µm)
Response time	< 10 s (95%)
Tilt error	< ± 2 %
Nonlinearity	< ± 1% (100...1000 W/m ²)
Areas of application	Temperature: -40...+80 °C
Supply	24 VDC (8...30 VDC)
Power consumption	< 48 mW (at 12 VDC)
Measuring elements	Thermos flask
Measuring principle	Thermal differential measurement
Dimensions	Max. Ø 92 mm; approx. H 95 mm
Protection class	IP67
Weight	Approx. 0.64 kg
Standards and norms	ISO 9060 "First Class"
Accessories (order separately)	32.14581.060000 Cable 10 m, M12 connector, 5-pin 32.05005.001500 Cable 15 m, M12 connector, 5-pin

As of June 9, 2026