

16131.5 PYRANOMETER



"First Class" Pyranometer

16131.5 digital pyranometer series is a range of high-accuracy digital solar radiation sensors.

It is "First Class" according to the WMO guide and ISO 9060:1990 standard and "Spectrally Flat Class B" in the 2018 revision.

Version 00.16131.501030, equipped with an on-board heater, is compliant in its standard configuration with the requirements for "Class B" PV monitoring systems of the IEC 61724-1:2017 standard.

The 16131.5 measures the solar radiation received by a plane surface, in W/m^2 , from a 180° field of view angle. Various outputs are available, both digital and analogue, for ease of integration.

- Best measurement accuracy in "First Class"
- Improved response time
- With 00.16131.501030's on-board heater: compliant with IEC 61724-1 Class B in its standard configuration

APPLICATIONS

- PV System Performance Monitoring
- Professional solar measurements
- Simulated solar tests (laboratory)
- Meteorological Networks

Professional Line	16131.5
Id-No.	00.16131.501040: Digital sensor with analogue 4-20 mA output 00.16131.501000: Analogue sensor passive millivolt (mV) output
Measuring range	0...3000 W/m^2 · global radiation within a range of 285...3000 nm
Directional answer	$\pm 20 \text{ W/m}^2$
Resolution	0.01 W/m^2
Spectral sensitivity	$\pm 3\%$ (0.35...1.5 μm)
Response time	10 s (95 %)
Inclination error	$\pm 2\%$
Non-linearity	$\pm 1\%$ (100...1000 W/m^2)
Range of application	temperatures -40...+80 °C
Power supply	24 VDC (8...30 VDC)
Power consumption	48 mW (at 12 VDC)
Measuring elements	thermopile
Measuring principle	thermal difference measurement
Dimensions	max. Ø 92 mm · approx. H 95 mm
Protection class	IP67
Weight	approx. 0.64 kg
Standards	ISO 9060 „First Class“

00.16131.501030 Cable 10 m, M12 plug connector, 5-pin

00.16131.501000 Cable 4 m, M12 plug connector, 5-pin

