

8091 HUMIDITY-TEMPERATURE SENSOR



Small, light, compact

Special resistance to airborne pollutants as a result of the use of a high-quality measuring element! This ensures - in combination with the high-quality electronics - excellent measuring accuracy and long-term stability. As a consequence, the sensor (8091) is particularly appropriate for measurements outdoors, in various areas of application.

- Small, light, compact
- Simple mounting, very robust, low-maintenance
- Low power consumption
- Good dynamic behaviour
- Reliable membrane filter as protection against atmospheric pollutants
- High long-term stability

APPLICATIONS

- Building services engineering
- Industry

Professional Line	8091
Id-No.	00.08091.000042 00.08091.000012
Meas. range air temperature	-30...+70 °C
Meas. range rel. humidity	0...100 % r. h.
Accuracy air temperature	± 0.3°C (4...20 mA); plus ± 0.007 K/K (10°C, > 40°C)
Accuracy rel. humidity	± 2 % r. h. (5...95 % r. h. at 10...40°C); plus 0.1 %/ K (10°C, >40°C)
Response time	1 min

Continued on page 2

Professional Line	8091
Long-term stability	typical under normal conditions 1% r. h./ year
Output	00.08091.000042: 4...20 mA 00.08091.000012: 0...10 VDC
Supply voltage	00.08091.000042: 12...30 VDC 00.08091.000012: 15...30 VDC
Power consumption	max. 45 mA
Measuring elements	capacitive • Pt100 • IEC 751 class B
Dimensions	H 180 mm • Ø 20 mm
Housing	aluminium • lacquered • grey-white
Protection class	IP 65 • membrane filter as sensor protection IP 30
Weight	0.34 kg
Standards	CE/ EMV: DIN 50082-2 • EN 55011 cl. B
Accessories (order separately)	00.08141.600000 Sensor shelter with natural ventilation 00.08141.600004 Sensor shelter with artificial ventilation 67.01002.056041 Cable: 4 x AWG 20 C UL sw for 00.08091.000042 67.01002.056081 Cabel: 8 x AWG 20 C UL sw for 00.08091.000012

As of: 13.06.2024